

## VECTOR GEN 2 CRB

.45ACP

9mm

10mm

.40S&W



### PRODUCT FEATURES

- ▶ Patented KRISS Super V Recoil Mitigation System
- ▶ Toolless caliber interchangeability
- ▶ Glock magazine compatible
- ▶ Full length MIL-STD 1913 Picatinny top rail
- ▶ MIL-STD 1913 Picatinny bottom rail
- ▶ MIL-STD 1913 Picatinny side accessory rail (optional)
- ▶ DEFIANCE® flip-up sights
- ▶ KRISS Vector enhanced shroud
- ▶ DEFIANCE® DS150 stock
- ▶ Integrated M4 buffer tube adaptor
- ▶ Smooth pivoting trigger with audible and tactile reset
- ▶ Ambidextrous short throw safety lever
- ▶ 4-pin toolless disassembly
- ▶ Charging handle / brass check function

### PRODUCT SPECIFICATIONS

<b>Operating system</b>	Closed bolt, delayed-blowback patented KSV System			
<b>Caliber</b>	.45ACP	9mm	10mm	40S&W
<b>Overall length</b>	Extended: 38.5 in / 978 mm Collapsed: 35.25 in / 895 mm			
<b>Overall height</b>	6.8 in / 175 mm			
<b>Barrel length</b>	16.5 in / 406 mm			
<b>Barrel twist</b>	1:16" RH	1:10" RH	1:10" RH	1:10" RH
<b>Weight (unloaded)</b>	8.3 lbs / 3.7 kg			
<b>Frame material</b>	Advanced metal components Advanced polymer composite			
<b>Capacity</b>	13+1	17+1	15+1	15+1
<b>Magazines</b>	G21 13 rds KRISS MagEx 25 rds	G17 17 rds G17 33 rds	G20 10 rds G20 15 rds	G22 15 rds

All specifications subject to change.

"GLOCK" is a federally registered trademark of Glock, Inc. and is one of many trademarks owned by Glock Inc. or Glock Ges.m.b.H. Neither KRISS USA nor this datasheet is affiliated in any manner with, or otherwise endorsed by, Glock, Inc. or Glock Ges.m.b.H. The use of "Glock" on this page is merely to advertise the sale of Glock pistols, parts, or components