

VECTOR GEN 2 SBR : Olive Drab

.45 ACP

9mm

10mm

.40S&W



PRODUCT FEATURES

- ▶ Patented KRIS Super V Recoil Mitigation System
- ▶ Toolless caliber interchangeability
- ▶ Glock magazine compatible
- ▶ Full length MIL-STD 1913 Picatinny top rail
- ▶ MIL-STD 1913 Picatinny bottom rail
- ▶ MIL-STD 1913 Picatinny side accessory rail (optional)
- ▶ DEFIANCE® flip-up sights
- ▶ KRIS Vector folding stock
- ▶ Integrated M4 buffer tube adaptor
- ▶ Smooth pivoting trigger with audible and tactile reset
- ▶ Ambidextrous short throw safety lever
- ▶ 4-pin toolless disassembly
- ▶ Charging handle / brass check function

PRODUCT SPECIFICATIONS

| | | | | |
|--------------------------|---|--------------------------|--------------------------|------------|
| Operating system | Closed bolt, delayed-blowback patented KSV System | | | |
| Caliber | .45ACP | 9mm | 10mm | 40S&W |
| Thread pitch | M16X1 LH | 1/2X28 RH | 9/16X24 RH | 9/16X24 RH |
| Overall length | Unfolded: 25 in / 633 mm Folded: 15.5 in / 394 mm | | | |
| Overall height | 6.8 in / 175 mm | | | |
| Barrel length | 5.5 in / 140 mm | | | |
| Barrel twist | 1:16" RH | 1:10" RH | 1:10" RH | 1:10" RH |
| Weight (unloaded) | 8.3 lbs / 3.7 kg | | | |
| Frame material | Advanced metal components Advanced polymer composite | | | |
| Capacity | 13+1 | 17+1 | 15+1 | 15+1 |
| Magazines | G21 13 rds KRIS MagEx 25 rds | G17 17 rds G17 33 rds | G20 10 rds G20 15 rds | G22 15 rds |

All specifications subject to change.

"GLOCK" is a federally registered trademark of Glock, Inc. and is one of many trademarks owned by Glock Inc. or Glock Ges.m.b.H. Neither KRIS USA nor this datasheet is affiliated in any manner with, or otherwise endorsed by, Glock, Inc. or Glock Ges.m.b.H. The use of "Glock" on this page is merely to advertise the sale of Glock pistols, parts, or components.